



# TECHNICAL DATA SHEET

**PRODUCT NAME:**

**WB Wicked Seal**

**PRODUCT CODE:**

210675

**CATEGORY:**

**Water Base Sealer**



## Limitations:

**Do not** use on surfaces to receive concrete overlays or additional toppings, coatings, sealers, or ceramic tile without proper surface preparation.

**Do not** use in areas that require resistance to solvents.

**Do not** subject to rain or water until it dries completely.

**Do not** apply in highly humid conditions. For maximum life expectancy, routinely sweep and wash floors with appropriate cleaners and detergents.

---

## WB Wicked Seal

**WB Wicked Seal** is a 20% Acrylic Sealer Designed for Interior and exterior use over all Wicked Kolor Overlay Systems as well as bare concrete for sealing and dust proofing.

**WB Wicked Seal** is a water-based, low-VOC, non-flammable, and non-hazardous acrylic sealer designed to provide a satin finish to interior and exterior applications.

Wicked Kolors Stains may be utilized in this sealer.

WB Wicked Seal may be applied to bare concrete without a primer and is best applied by spraying.

### **WHERE TO USE:**

Use on exterior and interior odor sensitive locations, such as schools, homes, apartments, offices, and restaurants.

Use WB Wicked Seal as Step 4 of the WK overlay system.



Distributed By: Epoxy Depot  
[www.epoxydepotusa.com](http://www.epoxydepotusa.com)

Epoxy Depot  
235 W Penn Ave  
Cleona, PA 17042

# PRODUCT APPLICATION

Apply a continuous, uniform film by low-pressure spray, short-nap roller, or lamb's wool applicator. A low-pressure hand-pump sprayer is recommended for best results.

For curing, only 1 coat is necessary. Apply evenly as soon as possible after final finishing.

To seal and dust proof, 2 coats must be applied at the recommended rates. Apply the second application when all trades are completed, and the site is ready for occupancy.

WB Wicked Seal applied at 40 to 50° F (4 to 10° C) may retain a white appearance for extended periods, depending on temperature variations. This condition should be temporary. Warmer temperatures will allow the material to dry clear.



## KEY FEATURES

- Low odor, and very low VOC's
- May be applied to many porous surfaces including, stone, brick, manufactured stone, overlays and many types of tile.
- Single component-Quick drying formulation
- Low water pick up.
- Exterior and Interior compatible
- Wicked Overlay Step 4

## TECHNICAL DATA SPECIFICATION

### SPECS

**\*Coverage: 300-400 sq. ft. /Gal per coat.**

**\*Appearance (cured): satin**

**\*Appearance (wet): milky liquid**

**\*Set to Touch: 30 Minutes**

**\*Set to Recoat: 1.5 Hours**

**\*Set for Light Foot Traffic: 4 Hours**

**\*Set for Normal Traffic: Overnight**

**\*Maximum Hardness: 7 Days**

**\*Shelf Life- 1 year in original unopened container.**

### First Aid

In case of skin contact, wash thoroughly with soap and water. For eye contact, flush immediately with plenty of water for at least 15 mins. For respiratory problems, remove person to fresh air. Contact Physician Immediately. Wash clothes before re-use.

**Keep out of reach of children**

**Substrate Temp Conditions @70 F.**



Distributed By: Epoxy Depot  
www.epoxydepotusa.com

Epoxy Depot  
235 W Penn Ave  
Cleona, PA 17042