



WICKED STAIN

PRODUCT INFORMATION

Name: Wicked Stains Step 3

Generic Type: Waterborne Acrylic.

General Properties: A decorative stain for concrete surfaces. Wicked Stains is water submersible, alkali, weather and UV light resistant. These stains require a top coat and are compatible with solvent based, water-based, single and two component products, including but not limited to urethanes, acrylics and epoxy sealers.

Colors: All the colors Wicked Stains Step 3 are compatible with one and another in both the dry and wet stage.

Colors Retention: All the colors formulated for Wicked Stains have been specially selected to produce the most durable light fast and alkali resistant coating available.

HIGHLIGHTS

- Fast Air Dry
- Compatible with Wicked Texture, overlays as topical stain and as integral color
- Low odor
- Low VOC
- Compatible with neutralized acid based stains
- May Be Applied over previously sealed surface

COVERAGE

Package Size	Total Yield	Coverage
4 ounce s	20 ounces	35-50 sq ft
1 quart	1.25 gallons	250-400sq ft
1 gallon	5 gallons	1000-1400 sq ft
5 gallons	25 gallons	5000-8000 sq ft





WICKED STAIN

AREA PREPARATION

Be sure to mask or cover areas that are not intended to be stained. but not limited to door frames, doors, walls and windows

Surface Preparation:

Staining a Concrete Floors should be viewed as the most important. Proper floor preparation results in the stains longevity, minimizes potential failures and creates the best environment for an aesthetically pleasing work of art. In short, the more detail and time allotted to this phase of the project will dramatically affect the appearance and durability of the finished floor .

The surface must be free of all foreign materials that would inhibit the absorption of Wicked Stain.

PRECAUTIONARY STATEMENT

Wash hands thoroughly after handling. Wear protective clothing, gloves, safety glasses, and use a respirator. Do not eat, drink or smoke when using this product. Store in a well-ventilated place. Make sure all HVAC vents are covered prior to use to prevent fumes from traveling. Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering - STOP - ventilation is inadequate. Leave area immediately. If the work area is not well ventilated, do not use this product. Keep container tightly closed. Dispose of contents/ container according to local, state and federal regulations.

FIRST AID

INHALATION: Remove to fresh air immediately. If breathing is difficult, administer oxygen. Get Medical Help.

INGESTION: Do not induce vomiting. Get Immediate Medical Help.

EYES: Flush with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

SKIN: Wash with soap and water. Remove and launder contaminated clothing before reuse.

IN CASE OF FIRE

Use foam, dry chemical, sand, earth, or CO2 to extinguish. Over heated or burning product will boil off flammable fumes and heavy smoke.

